



AGRCU0101
Incline



AGRCU0102
Peak




AGRCU0103
Alpine



AGRCU0104
Ridge



AGRCU0106
Belle



CORNICE SPECIFICATIONS

Dimensions (nominal)	7" Width x 48" Length x 5mm Thick Overall
Construction	Waterproof Rigid Core, 4mm thick plus 1mm premium pad
Finish Coat	Polyurethane Coating
Wear Layer	12mil
Texture	Embossed
Profile	Micro Bevel
Installation	Angle/Angle
Warranty	25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family
Packaging	23.892 sf/ctn, 45 ctn/plt, 1075.14 sf/plt



INSTALLATION FAST FACTS

Read Complete Instructions Before Installing

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Relative Humidity: 35%-55%
- Recommended Room Temp: 60°F -85°F after install
- Expansion Space: 1/4" gap
- No transitions required in rooms under 2,500 sf

COORDINATING TRIMS AVAILABLE

- T-Mold, Reducer, Quarter Round, End Cap, Stair Nose, QNose

FEATURES & BENEFITS

- Dimensionally stable rigid core construction
- Premium IXPE attached pad reduces sound transfer and adds comfort underfoot
- Waterproof core technology protects against spills
- Polyurethane finish provides extra scratch resistance
- Simple locking system allows for easy installation

DISTRIBUTED BY

T&A supply company, Inc.