



VIEW COLLECTION



AGRCU0205  
Whiskey

AGRCU0202  
Ozet

AGRCU0203  
Cruiser

AGRCU0204  
Crescent

AGRCU0201  
Stone

AGRCU0206  
Coho

## SPIRE SPECIFICATIONS

Dimensions (nominal)	9" Width x 60" Length x 5mm Thick Overall
Construction	Waterproof Rigid Core, 4mm thick plus 1mm premium pad
Finish Coat	Polyurethane Coating
Wear Layer	20mil
Texture	Embossed
Profile	Micro Bevel
Installation	Angle/Angle
Warranty	30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family
Packaging	22.43 sf/ctn, 60 ctn/plt, 1346 sf/plt



## FEATURES & BENEFITS

- Dimensionally stable rigid core construction
- Premium IXPE attached pad reduces sound transfer and adds comfort underfoot
- Waterproof core technology protects against spills
- Polyurethane finish provides extra scratch resistance
- Longer and wider planks offer a modern design

## INSTALLATION FAST FACTS

Read Complete Instructions Before Installing

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Relative Humidity: 35%-55%
- Recommended Room Temp: 60° F - 85° F after install
- Expansion Space: 1/4" gap
- No transitions required in rooms under 2,500 sf

## COORDINATING TRIMS AVAILABLE

- T-Mold, Reducer, Quarter Round, End Cap, Stair Nose, QNose

Additional Specifications, Full Installation Instructions & Warranty Information Available Online [www.tasupply.com](http://www.tasupply.com)

DISTRIBUTED BY

**TA supply company, Inc.**