


VIEW COLLECTION



NFRCU0101  
Incline

NFRCU0102  
Peak

NFRCU0106  
Belle

NFRCU0107  
Mammoth

NFRCU0108  
Bridger

CORNICE SPECIFICATIONS

Construction	Waterproof Rigid Core
Dimensions (nominal)	7" Wide x 48" Long, 182 mm x 1220 mm
Overall Thickness	5 mm (includes 1 mm pad)
Wear Layer	12 mil
Finish Coat	Polyurethane
Edge Profile	4-Sided Micro Bevel
Texture	Embossed
Installation	Angle/Angle
Packaging	26.26 sf/ctn, 50 ctn/plt, 1313 sf/plt
Warranty	25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family



INSTALLATION FAST FACTS **Read Complete Instructions Before Installing**

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Relative Humidity: 35%-55%
- Recommended Room Temp: 60° F - 85° F after install
- Expansion Space: 1/4" gap
- No transitions required in rooms under 2,500 sf

COORDINATING TRIMS AVAILABLE

- T-Mold, Reducer, Quarter Round, End Cap, Stair Nose, QNose

FEATURES & BENEFITS

- Dimensionally stable rigid core construction
- Premium IXPE attached pad reduces sound transfer and adds comfort underfoot
- Waterproof core technology protects against spills
- Polyurethane finish provides extra scratch resistance
- Simple locking system allows for easy installation

DISTRIBUTED BY

