



VIEW COLLECTION



NFRCU0205
Whiskey

NFRCU0202
Ozet

NFRCU0203
Cruiser

NFRCU0204
Crescent

NFRCU0207
Pyramid

NFRCU0208
Cairns

SPIRE SPECIFICATIONS

Construction	Waterproof Rigid Core
Dimensions (nominal)	9" Wide x 60" Long, 230 mm x 1524 mm
Overall Thickness	5 mm (includes 1 mm pad)
Wear Layer	20 mil
Finish Coat	Polyurethane Coating
Edge Profile	4-Sided Micro Bevel
Texture	Embossed
Installation	Angle/Angle
Packaging	26.37 sf/carton - 48 carton/pallet - 1265.76 sf/pallet
Warranty	30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family



FEATURES & BENEFITS

- Dimensionally stable rigid core construction
- Premium IXPE attached pad reduces sound transfer and adds comfort underfoot
- Waterproof core technology protects against spills
- Polyurethane finish provides extra scratch resistance
- Longer and wider planks offer a modern design

INSTALLATION FAST FACTS **Read Complete Instructions Before Installing**

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Relative Humidity: 35%-55%
- Recommended Room Temp: 60° F -85° F after install
- Expansion Space: 1/4" gap
- No transitions required in rooms under 2,500 sf

COORDINATING TRIMS AVAILABLE

- T-Mold, Reducer, Quarter Round, End Cap, Stair Nose, QNose

DISTRIBUTED BY

TAS supply company, Inc.