



NFRCU0310
Texas Pine

NFRCU0311
Hampshire Oak

WYNN SPECIFICATIONS

Construction	Waterproof Rigid Core
Dimensions	7" Wide x 48" Long, 182 mm x 1220 mm
Overall Thickness	4.2 mm (included 1 mm pad)
Wear Layer	20 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Packaging	31.11 sf/carton - 50 carton/pallet - 1555.5 sf/pallet
Installation	Angle/Angle
Warranty	25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family



FEATURES & BENEFITS

- Dimensionally stable rigid core construction
- Premium IXPE attached pad reduces sound transfer and adds comfort underfoot
- Waterproof core technology protects against spills
- Polyurethane finish provides extra scratch resistance
- Simple locking system allows for easy installation

INSTALLATION FAST FACTS

Read Complete Instructions Before Installing

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Relative Humidity: 35%-55%
- Recommended Room Temp: 60° F - 85° F after install
- Expansion Space: 1/4" gap
- Transitions required for rooms larger than 50' W x 50' L

COORDINATING TRIMS AVAILABLE

- T-Mold, Reducer, Quarter Round, End Cap, Stair Nose, QNose

Additional Specifications, Full Installation Instructions & Warranty Information Available Online www.tasupply.com

DISTRIBUTED BY

T&A supply company, Inc.